

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

DATE MAILED: 07/22/2005

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/005,649	12/03/2001	Younglok Kim	1-2-172.1US	7657
24374	7590 07/22/2005		EXAMINER	
VOLPE AND KOENIG, P.C.			SHAH, CHIRAG G	
DEPT. ICC				
UNITED PLAZA, SUITE 1600			ART UNIT	PAPER NUMBER
30 SOUTH 17TH STREET			2664	
PHILADELP	HIA, PA 19103			

Please find below and/or attached an Office communication concerning this application or proceeding.



	Application No.	Applicant(s)				
	10/005,649	KIM ET AL.				
Office Action Summary	Examiner	Art Unit				
	Chirag G. Shah	2664				
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address				
A SHORTENED STATUTORY PERIOD FOR REPLY THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a reply - If NO period for reply is specified above, the maximum statutory period v Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	36(a). In no event, however, may a reply be time within the statutory minimum of thirty (30) days will apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	nely filed s will be considered timely. the mailing date of this communication. D (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on 03 De	ecember 2001.					
•						
Disposition of Claims						
 4) Claim(s) 1-16 is/are pending in the application. 4a) Of the above claim(s) is/are withdraw 5) Claim(s) is/are allowed. 6) Claim(s) 1-16 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/or 	vn from consideration.	·				
Application Papers						
9)☐ The specification is objected to by the Examine 10)☒ The drawing(s) filed on 03 December 2001 is/an Applicant may not request that any objection to the Replacement drawing sheet(s) including the correction 11)☐ The oath or declaration is objected to by the Examine 10.	re: a) ☐ accepted or b) ☒ object drawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).				
Priority under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received.						
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:					
raper No(s)/Iviali Date	• o) [_] Other:					

DETAILED ACTION

Drawings

1. Figure 1 should be designated by a legend such as --Prior Art-- because only that which is old is illustrated. See MPEP § 608.02(g). Corrected drawings in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. The replacement sheet(s) should be labeled "Replacement Sheet" in the page header (as per 37 CFR 1.84(c)) so as not to obstruct any portion of the drawing figures. If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 1-16 rejected under 35 U.S.C. 103(a) as being unpatentable over Whinnett et al. (U.S. Patent No. 6,317,411), hereinafter referred as Whinnett in view of Stewart et al. (U.S. Patent No. 6,339,612), hereinafter referred as Stewart.

Regarding claim 1, Whinnett discloses in fig. 5 of a method for transmitting data symbols [S1 through S4, see fig. 5] in a CDMA communication system [col. 1, lines 20-24] including a

transmitter [col. 5, lines 18-20, the transmitter of fig. 5 transmits signals to antenna 120 of the subscriber unit] having an antenna array [antennas 100-106, fig. 5] and a receiver [the subscriber unit (receiver) of fig. 7, receives and demodulates a signal transmitted by the transmitter of fig. 5, see col. 6, lines 44-46], the method comprising the steps of:

generating a first [S1S1, fig. 5] and second [S2S2, fig. 5] data field of symbols [transformer 88 implemented with space-time coders such as 60 of fig. 3, provide a first output S1S1S2S2, see fig. 5 and col. 5, lines 35-42];

encoding said first (S1S1, fig. 5) and second data (S2S2, fig. 5) field producing complex conjugates of the symbols of said first (S1*S1*, fig. 5) and second (-S2*-S2, fig. 5) data field [transformer 88 implemented with space-time coders encodes first S1S1 and second S2S2 and producing -S2*-S2 of first and second data fields, see fig. 5, col. 5, lines 38-42];

transmitting from the said transmitter [col. 5, lines 18-20, the transmitter of fig. 5 transmits signals] a first communication burst [r1(S1S1S2S2) burst, fig. 5] including said first and second data fields [S1S1S2S2, fig. 5] over a first antenna [antenna 100, fig. 5] and a second communication burst [r2(-S2*-S2*S1*S1*) burst, fig. 5] produced using said complex conjugates of said first and second data fields [-S2*-S2*S1*S1*, fig. 5] over a second antenna [antenna 102, fig. 5]; and

receiving and decoding at said receiver (subscriber unit, fig. 7) said first [r1(S1S1S2S2) burst, fig. 5] and second communication bursts [r2(-S2*-S2*S1*S1*) burst, fig. 5] to recover said first and second data fields [as disclosed in col. 6, lines 44-

52 and fig. 7, subscriber unit receives and decodes a signal transmitted by the transmitter of fig. 5].

Whinnett fails to explicitly disclose of the first and the second data fields separated by a midamble over a first and second respective antennas.

Stewart teaches of a joint detection of data signals in a CDMA communication system.

Stewart discloses in col.3, lines 17-26 and fig. 1 of including a midamble portion in a burst (fig. 1) having data sub-burst 1 and data sub-burst 2. The midamble portion of the burst of fig. 1 received on each antenna provides a channel estimation function. Therefore, it would have been obvious to one of ordinary skills in the art at the time of the invention to modify the teachings of Whinnett to include the feature of a burst having a midamble portion within data sub-burst 1 and data sub-burst 2 as taught by Stewart. One is motivated as such in order to provide a means for channel estimation enabling an estimation of the complex-valued channel impulse response defined from each user to each antenna (Stewart, col. 3, lines 17-26).

Regarding claim 7, Whinnett discloses in fig. 5 of a CDMA [col. 1, lines 20-24] communication system including a base station [col. 5, lines 18-20, the transmitter of fig. 5 transmits signals] and a user equipment (UE) [subscriber unit, fig. 7 and col. 6, lines 44-46], comprising:

an encoder [transformer 88 implemented with space-time coders encodes, col. 5, lines 38-42] which encodes a first (S1S1, fig. 5) and second data field of symbols (S2S2, fig. 5) to produce complex conjugates of the symbols of said first (S1*S1*, fig. 5)

Art Unit: 2664

and second (-S2*-S2, fig. 5) data field [transformer 88 implemented with space-time coders encodes first S1S1 and second S2S2 and producing -S2*-S2 of first and second data fields, see fig. 5, col. 5, lines 38-42];

a first [antenna 100, fig. 5] and second antenna [antenna 102, fig. 5] of a transmitter which transmits RF signals including a first [r1(S1S1S2S2) burst, fig. 5] and second communication burst [r2, fig. 5], wherein said first communication burst [r1(S1S1S2S2) burst, fig. 5] including said first (S1S1, fig. 5) and second (S2S2, fig. 5) data fields is transmitted by said first antenna [antenna 100, fig. 5] and a second communication burst [r2(-S2*-S2*S1*S1*) burst, fig. 5] produced using said complex conjugates of said first and second data fields [-S2*-S2*S1*S1*, fig. 5] over a second antenna [antenna 102, fig. 5]; and

a receiver (subscriber unit, fig. 7) comprising a decoder which decodes said RF signals to recover said first [r1(S1S1S2S2) burst, fig. 5] and second [r2(-S2*-S2*S1*S1*) burst, fig. 5] data fields [as disclosed in col. 6, lines 44-52 and fig. 7, subscriber unit receives and decodes a signal transmitted by the transmitter of fig. 5].

Whinnett fails to explicitly disclose of the first and the second data fields separated by a midamble over a first and second respective antennas.

Stewart teaches of a joint detection of data signals in a CDMA communication system. Stewart discloses in col.3, lines 17-26 and fig. 1 of including a midamble portion in a burst (fig. 1) having data sub-burst 1 and data sub-burst 2. The midamble portion of the burst of fig. 1 received on each antenna provides a channel estimation function. Therefore, it

Art Unit: 2664

would have been obvious to one of ordinary skills in the art at the time of the invention to modify the teachings of Whinnett to include the feature of a burst having a midamble portion within data sub-burst 1 and data sub-burst 2 as taught by Stewart. One is motivated as such in order to provide a means for channel estimation enabling an estimation of the complex-valued channel impulse response defined from each user to each antenna (Stewart, col. 3, lines 17-26).

Regarding claim 12, Whinnett discloses in fig. 5 a transmitter [col. 5, lines 18-20, the transmitter of fig. 5 transmits signals] which transmits data symbols [S1S1S2S2, fig. 5] in a CDMA [col. 1, lines 20-24] communication system including a base station [col. 5, lines 18-20, the transmitter of fig. 5 transmits signals] and a user equipment (UE) [subscriber unit, fig. 7 and col. 6, lines 44-46], said transmitter [col. 5, lines 18-20, the transmitter of fig. 5 transmits signals] comprising:

an encoder [transformer 88 implemented with space-time coders encodes, col. 5, lines 38-42] which encodes a first (S1S1, fig. 5) and second data field of symbols (S2S2, fig. 5) to produce complex conjugates of the symbols of said first (S1*S1*, fig. 5) and second (-S2*-S2, fig. 5) data field [transformer 88 implemented with space-time coders encodes first S1S1 and second S2S2 and producing -S2*-S2 of first and second data fields, see fig. 5, col. 5, lines 38-42];

a first [antenna 100, fig. 5] and second antenna [antenna 102, fig. 5] of a transmitter which transmits RF signals including a first [r1(S1S1S2S2) burst, fig. 5] and second communication burst [r2(-S2*-S2*S1*S1*) burst, fig. 5], wherein said first

Art Unit: 2664

communication burst [r1(S1S1S2S2) burst, fig. 5] including said first (S1S1, fig. 5) and second (S2S2, fig. 5) data fields is transmitted by said first antenna [antenna 100, fig. 5] and a second communication burst [r2(-S2*-S2*S1*S1*) burst, fig. 5] produced using said complex conjugates of said first and second data fields [-S2*-S2*S1*S1*, fig. 5] over a second antenna [antenna 102, fig. 5]; and

Whinnett fails to explicitly disclose of the first and the second data fields separated by a midamble over a first and second respective antennas.

Stewart teaches of a joint detection of data signals in a CDMA communication system. Stewart discloses in col.3, lines 17-26 and fig. 1 of including a midamble portion in a burst (fig. 1) having data sub-burst 1 and data sub-burst 2. The midamble portion of the burst of fig. 1 received on each antenna provides a channel estimation function. Therefore, it would have been obvious to one of ordinary skills in the art at the time of the invention to modify the teachings of Whinnett to include the feature of a burst having a midamble portion within data sub-burst 1 and data sub-burst 2 as taught by Stewart. One is motivated as such in order to provide a means for channel estimation enabling an estimation of the complex-valued channel impulse response defined from each user to each antenna (Stewart, col. 3, lines 17-26).

Regarding claims 2, 8 and 13, Whinnett discloses wherein an encoder [transformer 88 implemented with space-time coders encodes, col. 5, lines 38-42] negates the complex conjugate of the second data field (-S2*-S2*, fig. 5)[see fig. 5 and col. 3, lines 5-10] as claims.

Art Unit: 2664

Regarding claims 3, 9, and 14, Whinnett further discloses in fig. 5 comprising the step of generating

said first [r1(S1S1S2S2) burst, fig. 5] by a first burst generator [transformer 88 and 90] and second [r2(-S2*-S2*S1*S1*) burst, fig. 5] communication burst by a second burst generator [transformer 88 and 90] wherein said first communication burst comprises said first data field (S1S1) followed by said second data field (S2S2); and

said second [r2(-S2*-S2*S1*S1*) burst, fig. 5]communication burst comprises said negative complex conjugate of said second data field (-S2*-S2*, fig. 5) followed by said complex conjugate of said first data field (S1*S1*, fig. 5).

Whinnett fails to explicitly disclose each of the first and the second communications burst having first and second data fields separated by a midamble over a first and second respective antennas.

Stewart teaches of a joint detection of data signals in a CDMA communication system.

Stewart discloses in col.3, lines 17-26 and fig. 1 of including a midamble portion in a burst (fig. 1) having data sub-burst 1 and data sub-burst 2. The midamble portion of the burst of fig. 1 for each burst received on each antenna provides a channel estimation function.

Therefore, it would have been obvious to one of ordinary skills in the art at the time of the invention to modify the teachings of Whinnett to include the feature of a burst having a midamble portion within data sub-burst 1 and data sub-burst 2 as taught by Stewart. One is motivated as such in order to provide a means for channel estimation enabling an estimation of the complex-valued channel impulse response defined from each user to each antenna (Stewart, col. 3, lines 17-26).

Art Unit: 2664

Regarding claim 4, Whinnett discloses of a subscriber unit receives and decodes a signal transmitted by the transmitter of fig. 5. Whinnett fails to explicitly disclose wherein said receiving and decoding step comprises: estimating a channel response of said first and second communication bursts using said bursts' midambles; and detecting the symbols of said first and second communication bursts in response to said channel response. Stewart discloses in col. 4, lines 51-55 and in col. 3, lines 17-26, of a DSP (fig. 4) receiver the receives signal vectors S(ka) (bursts) and extracts/decodes the midamble portion of each S(ka) and generates a channel estimate and impulse response from each user to antenna based on each burst. Stewart detects the symbols of the burst signals in response to the estimation by further discloses in col. 3, lines 22-40 that the DSP receiver includes a detector, which uses the resulting set of convolved signal vectors (bursts) to extract the data symbol information from each user. and outputs soft-decision symbol information for used in subsequent error control decoding. Therefore, it would have been obvious to one of ordinary skills in the art at the time of the invention to modify the teachings of Whinnett to include the feature of a burst having a midamble portion that enable detection of the symbols based on midamble portion as taught by Stewart. One is motivated as such in order to provide a means for channel estimation and jointly provide detection of data symbols transmitted over a communication channel (Stewart, col. 1, lines 7-11 and col. 3, lines 17-26).

Regarding claim 5, 10 and 15, Whinnett discloses wherein a base station [col. 6, lines 44-46, the transmitter of fig. 5 transmits signals to the subscriber unit, establishing that the

transmitter of fig. 5 is a base station which serves the user] includes said receiver [base station/transmitter unit of fig. 5 in a CDMA system inherently includes a receiver for receiving data via antenna 100-106] and a user equipment includes [subscriber unit, fig. 7 and col. 6, lines 44-46] said transmitter [subscriber unit in fig. 7 in a CDMA system inherently includes a transmitter for sending and receiving data via antenna 120].

Regarding claim 6, 11 and 16, Whinnett discloses wherein a user equipment (UE) [subscriber unit, fig. 7 and col. 6, lines 44-46] includes said receiver [antenna 120, fig. 7] and a base station includes said transmitter [col. 6, lines 44-46, the transmitter of fig. 5 transmits signals to the subscriber unit, establishing that the transmitter of fig. 5 is a base station which serves the user].

Conclusion

Any response to this action should be mailed to:

Commissioner of Patents and Trademarks Washington, D.C. 20231

Or faxed to:

(703)305-3988, (for formal communications intended for entry)

Or:

(703)305-3988 (for informal or draft communications, please label "Proposed" or "DRAFT")

Hand-delivered responses should be brought to Crystal Park II, 2021 Crystal Drive, Arlington, VA., Sixth Floor (Receptionist).

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Chirag G. Shah whose telephone number is 571-272-3144. The examiner can normally be reached on M-F 8:30-5:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Wellington Chin can be reached on 571-272-3134. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

cos

July 13, 2005

Chirag Shah